



JDYX2.E20624 Fuses, Supplemental - Component

[Page Bottom](#)

Fuses, Supplemental - Component

[See General Information for Fuses, Supplemental - Component](#)

BEL FUSE INC

E20624

206 VAN VORST ST
JERSEY CITY, NJ 07302 USA

With pigtail leads: Micro, Type MFE, 0.05 -7A, 125 Vac .

Micro, Types MBS, MBSP, MS, 0.05-7A, 125 Vac/dc; Types MBQ, MBQP, MQ, 0.05-15A, 125 Vac/dc; Type WP91813 followed by L1-L17, 0.125-15 A, 125 Vac/dc .

Micro, Types MRT, MRTU, 0.080-6.3A, 250 or 277 Vac.

Miniature, Type GSM, 10-20A, 250 Vac.

Micro, Type TCQ and TCQP, 0.125-5.0A, 300 Vac .

Micro, Cat. No. 1SM followed by suffix numbers; 0-7A, 125 Vac .

Micro, Cat. No. RRT, 0.08-6.3A, 250 Vac.

Miniature, Types GSA, GSA-R, GSAP, GSAP-R, 10-15A, 250 Vac .

Miniature, Types 5HT, 5HT-R, 5HTP, 5HTP-R, 0.25-6.3A, 250 Vac, 600 Vac, 8-10 A, 250 Vac.

Miniature, Types 2JQ, 2JQ-R, 3JQ, 3JQ-R, 0.1-7A, 350 Vac, 140 Vdc; Types 5JQ, 3JQ-P, 2-5A, 350Vac/140Vdc.

Miniature, Types 2JS, 2JS-R, 3JS, 3JS-R, 0.1-7A, 350 Vac, 140 Vdc.

Miniature, Types 3SF, 3SFP, 0.315-10A, 250 Vac .

Miniature, Types 5HF, 5HF-R, 5HFP, 5HFP-R, 0.1-10A, 250 Vac .

Miniature, Types 5SF, 5SF-R, 5SFP, 5SFP-R, 0.08-10A, 250 Vac .

Miniature, Types 5ST, 5ST-R, 5STP, 5STP-R, 0.063-10A, 250 Vac.

Miniature, Types 5TT, 5TT-R, 5TTP, 5TTP-R, 10A, 125 Vac.

Miniature, Types 33G, 33P, 0.5-15A, 300 Vac.

Miniature, Cat. Nos. 300V, 300VP, 0.1-5 amp, 300 Vac.

Supplemental, Types RJS, RJS-R, 0.1-5A, 600 Vac.

Miscellaneous, Types BER, DJB, 0.25-10A, 125 Vac.

Supplemental, Types 5ET, 5ET-R, 5ETP, 5ETP-R, 1-6.3A, 250 Vac.

Supplemental, Types 5VT, 5VT-R, 5VTP, 5VTP-R, 1-6.3A, 250 Vac.

Micro, Types MRF, MRFU, 0.05-6.3A, 350 Vac.

Micro, Type RS, 0.1-5 A, 250 Vac.

Micro, Types RST, RSTU, 0.08-6.3A, 277 Vac.

Surface mounts: Micro, Types C2Q, C2J, C2QC, C2F, 0.25-4A, 32 Vac, 63 Vdc, 5A, 32 Vac/dc.

Micro, Type SSQ, 15A, 86 Vdc.

Micro, Type SMP, 0.5- 2.0 A, 600 Vac, 125 Vdc.

Micro, Type SMP, 2.2A, 600Vac, 125 Vdc.

Micro, Types C1S, C1SC, C1T, 0.75-5A, 63 Vac/dc.

Micro, Types C1Q, C1J, C1QC, C1F, 7 A, 63 Vac/dc.

Micro, Type SMM, 10-30A, 250 Vac, 125 Vac, 72 Vdc, 65 Vdc.

Microfuse, Type C1H, 10-30A, 32 Vdc, 125 Vac.

Note - Cat. Nos. with suffix -R indicates construction with lead-free solder.

Marking: Company name and type or catalog designation.

Last Updated on 2012-04-16

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

©2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".