



JDYX7.E20624 Fuses, Supplemental Certified for Canada

Page Bottom

Fuses, Supplemental Certified for Canada

[See General Information for Fuses, Supplemental Certified for Canada](#)

BEL FUSE INC

E20624

206 VAN VORST ST
JERSEY CITY, NJ 07302 USA

Micro, cartridge enclosed, nonrenewable:

Type or Cat. No.	Size	Amps	V AC
C1Q, C1J	Micro	0.25-5	63dc
RGS+, RGS-R+	4.5x19.5mm	0.1-5	250
SSQ	Micro	1.1-12	125ac/86dc
SSQ	Micro	0.1-7	125ac/dc
8AG, 8AP	Miniature	0.75-2	250
8AG, 8AP	Miniature	2.5-7	125
8AG, 8AP	Miniature	0.032-0.75	250
5MF, 5MF-R, 5MFP, 5MFP-R	Miniature	0.05-3	250
5MF, 5MF-R, 5MFP, 5MFP-R	Miniature	3.1-8	125
5MT, 5MT-R, 5MTP, 5MTP-R	Miniature	1-5	125
5MT, 5MT-R, 5MTP, 5MTP-R	Miniature	0.05-0.8	250
5MT, 5MT-R, 5MTP, 5MTP-R	Miniature	1-3	
5MT, 5MT-R, 5MTP, 5MTP-R	Miniature	3.1-5	125
5TT, 5TT-R	Miniature	0.05-5	250
5TT, 5TT-R	Miniature	6-8	125
5TTP, 5TTP-R	Miniature	0.05-3	250
5TTP, 5TTP-R	Miniature	3.1-81	125
3AB, 3AB-R, 3ABP +, 3ABP-R+	Miniature	0.1-20	250
MJR, WP90109L1	Miniature	0.35	250
MJS, MJS-R, WP90400, WP90400-R	Miniature	0.1-7	250
3AG, 3AG-R, 3AP, 3AP-R	Miniature	0.1-10	250
3AG, 3AG-R, 3AP, 3AP-R	Miniature	12-15	125
3CB, 3CPB	Miniature	0.062-8	125
GSA, GSAP	Miniature	0.062-8	250
MRQ, MRQP	Micro	0.25-6.3	250
SST	Micro	0.375	125ac/125dc
3SB, 3SB-R, 3SBP, 3SBP-R	Miniature	0.05-8	250ac
3SB, 3SB-R, 3SBP, 3SBP-R	Miniature	8.1-15	125ac

+A Pigtail leads.

Note - Cat. Nos. with suffix -R indicates construction with lead-free solder.

Last Updated on 2006-07-28

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

©2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition,

