

SERIES: PDRB-100 | DESCRIPTION: AC-DC DIN RAIL POWER SUPPLY

FEATURES

- universal input range (85 ~ 264 Vac)
- IEC/EN/UL 62368 certified
- designed to meet 61558 system requirements
- over Voltage Category (OVC) III design
- over voltage, over current, and short circuit protections
- 4kVac isolation input to output
- withstand up to 300 Vac input surge events
- Class B emissions




MODEL	output ¹ voltage		output current max (A)	output power max (W)	ripple and noise ² max (mVp-p)	efficiency ³ typ (%)
	(Vdc)	range (Vdc)				
PDRB-100-12	12	12.0 ~ 13.8	7.5	90.0	120	88
PDRB-100-15	15	13.5 ~ 18.0	6.5	97.5	120	89
PDRB-100-24	24	21.6 ~ 29.0	4.2	100.8	150	90
PDRB-100-48	48	43.2 ~ 55.2	2.1	100.8	240	90

Notes:

1. Output adjustable via built-in trimpot. The actual adjustment range may extend beyond the values listed and care should be taken to ensure the output voltage and output power do not exceed stated limits.
2. At full load, nominal input, 20 MHz bandwidth oscilloscope.
3. At 230 Vac input.

PART NUMBER KEY



INPUT

parameter	conditions/description	min	typ	max	units
input voltage	ac input	85		264	Vac
	dc input	120		370	Vdc
frequency		47		63	Hz
current	at 115 Vac			3.0	A
	at 230 Vac			1.6	A
inrush current	at 115 Vac		35		A
	at 230 Vac		70		A
leakage current	at 240 Vac			0.5	mA

OUTPUT

parameter	conditions/description	min	typ	max	units
capacitive load	12 Vdc output models			10,000	μF
	15 Vdc output models			6,400	μF
	24 Vdc output models			2,500	μF
	48 Vdc output models			1,100	μF
initial set point accuracy	0% ~ 100% load		±2		%
line regulation	at rated load		±0.5		%
load regulation	at 230 Vac		±1.5		%
start-up time				3	s
hold-up time	at 230 Vac		30		ms
switching frequency			65		kHz
temperature coefficient			±0.03		%/°C
no load power consumption	at 230 Vac				
	12 Vdc, 15 Vdc output models			0.3	W
	24 Vdc output models			0.35	W
	48 Vdc output models			0.4	W

PROTECTIONS

parameter	conditions/description	min	typ	max	units
over voltage protection	12 Vdc output models			20	Vdc
	15 Vdc output models			25	Vdc
	24 Vdc output models			35	Vdc
	48 Vdc output models			60	Vdc
over current protection	auto recovery	110		200	%
short circuit protection	continuous, auto recovery, hiccup				

SAFETY & COMPLIANCE

parameter	conditions/description	min	typ	max	units
isolation voltage	input to output 5 mA for 1 minute	4,000			Vac
safety approvals	certified to 62368: IEC, EN, UL/cUL				
safety class	Class II				
conducted emissions	CISPR32/EN55032 CLASS B				
radiated emissions	CISPR32/EN55032 CLASS B				
ESD	IEC/EN61000-4-2 Contact $\pm 6\text{KV}$ /Air $\pm 8\text{KV}$ perf. Criteria A				
radiated immunity	IEC/EN61000-4-3 10V/m perf. Criteria A				
EFT/burst	IEC/EN61000-4-4 $\pm 4\text{KV}$ perf. Criteria A				
surge	IEC/EN61000-4-5 line to line $\pm 2\text{KV}$ perf. Criteria A				
conducted immunity	IEC/EN61000-4-6 10Vr.m.s perf. Criteria A				
voltage dips and interruption	IEC/EN61000-4-11 0%, 70% perf. Criteria A				
MTBF	as per MIL-HDBK-217F at 25°C	300,000			hours
RoHS	yes				

ENVIRONMENTAL

parameter	conditions/description	min	typ	max	units
operating temperature	see derating curve	-40		70	°C
storage temperature		-40		85	°C
storage humidity	non-condensing	0		95	%
altitude				2,000	m


MECHANICAL

parameter	conditions/description	min	typ	max	units
dimensions	70.00 x 92.66 x 58.00				mm
material	plastic, heat-resistant (UL94V-0)				
weight			235		g
cooling	natural convection				

MECHANICAL DRAWING


units: mm [inch]
ADJ: built-in trimpot
wire range: 24-12 AWG
tightening torque: Max 0.4 N·m
mounting rail: TS35
general tolerances: ±1.0 [±0.039]

TERMINAL CONNECTIONS	
TERMINAL	Function
1	AC (L)
2	AC (N)
3	+Vo
4	+Vo
5	-Vo
6	-Vo




DERATING CURVE

TEMPERATURE DERATING CURVE




INPUT VOLTAGE DERATING CURVE (25°C)




EFFICIENCY CURVES

EFFICIENCY VS INPUT LOAD (full load)



EFFICIENCY VS OUTPUT LOAD (Vin = 230 Vac)



REVISION HISTORY

rev.	description	date
1.0	initial release	11/25/2020
1.01	derating and efficiency curves updated	02/17/2022
1.02	UKCA mark added	04/11/2023

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.