

Applicant	Bel Fuse Inc. 300 Executive Drive, Suite 300 West Orange NJ 07052 United States of America
Manufacturer	Bel Fuse Inc. 300 Executive Drive, Suite 300 West Orange NJ 07052 United States of America
Factory	Bel Power Solutions, s.r.o. Areal ZTS 924 Dubnica nad Vahom 01841 Slovakia
Project Number	PRJ0091827
Product	AC/DC and DC/DC switching power supply
Model/Type Ref.	LKcdee-fgg
Ratings	Input: 100-240Vac 2.2-2.3A or 2.2-2.4A 50-60Hz / 88-300Vdc or 2.2-2.3A or 2.2-2.4A
Brandname / Trademark	  a bel group OR
Principal Characteristics	Output: One or two output; 28.25Vdc Max.; 20A Max.; Output power: 150W Max. Where the alpha characters are as follows: 'c' can be 4, 5, 6 or a higher number; 'd' can be 0 to 8 and may be followed by numbers 01 to 99; 'ee' can be 20, 40, 60, 70 to 99; 'f' can be -0, -1, -2, -3, -4, -5, -6, -7 or -9; 'gg' can be B1, B2, D, E, K, P, R, T or V. Refer to Test Report for further information.
A sample of the product was tested and found to be in conformity with	Safety EN IEC 62368-1:2024;A11
Validity	<i>This certificate documents conformity with the standards shown, and also applies as license for use of Nemko's name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation.</i> <i>New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.</i>
Additional Information	
Additional model(s)	See next pages

Signature



Juan Z Saussey
Certification department

Date of Issue

2025-12-05

Working for a more sustainable future
Please do not print



www.nemko.com

Product	AC/DC and DC/DC switching power supply
Variant	1
Model/Type Ref.	LKPcdee-fgg
Ratings.	Input: 200–240Vac 1.9–2.1A 50-60Hz
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Output: One or two output; 28.25Vdc Max.; 20A Max.; Output power: 280W Max. Where the alpha characters are as follows: 'c' can be 4, 5, 6 or a higher number; 'd' can be 0 to 8 and may be followed by numbers 01 to 99; 'ee' can be 20, 40, 60, 70 to 99; 'f' can be -0, -1, -2, -3, -4, -5, -6, -7 or -9; 'gg' can be B1, B2, D, E, K, P, R, T or V. Refer to Test Report for further information.
Product	AC/DC and DC/DC switching power supply
Variant	2
Model/Type Ref.	LScdee-fgg
Ratings.	Input: 100–240Vac 2.2–2.3A or 2.2–2.4A 50- 60Hz/95–300Vdc 2.2–2.3A or 2.2–2.4A
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Output: One or two output; 28.25Vdc Max.; 20A Max.; Output power: 100W Max. Where the alpha characters are as follows: 'c' can be 4, 5, 6 or a higher number; 'd' can be 0 to 8 and may be followed by numbers 01 to 99; 'ee' can be 20, 40, 60, 70 to 99; 'f' can be -0, -1, -2, -3, -4, -5, -6, -7 or -9; 'gg' can be B1, B2, D, E, K, P, R, T or V. Refer to Test Report for further information.

Signature



Juan Z Saussey

Certification department

Date of Issue

2025-12-05

*Working for a more sustainable future
Please do not print*



www.nemko.com