

ULP40CK SERIES



- ### Features
- Noncorrosive
 - Easy assembly
 - Low weight
 - Fully safe

| FOR ULP40, MULP40 SERIES | |
|---|--|
| Derating Guidelines | |
| ULP40/MULP40: De-rate to 70% of values mentioned in temperature de-rating curves of open frame models at all load and ambient conditions. | |
| Contents | |
| Mounting Base, Cover, Insulator, Fixing Screws | |
| Mechanical Dimensions | |
| Cover and Base Material | EG(Zintec)/CRCA/GI 1.0mm thick (Powder coating/ Passivation/ ED coating black) |
| Marked | A: PCB MTG; B: COVER MTG; C: SYSTEM MTG |
| All dimensions are in mm. General tolerance : +/-1.0 | |

Mechanical Drawing

| PARTS | DETAIL | QTY | LOCATION |
|--|--|-------|-----------------------|
| 1 COVER KIT BASE | SCREW_PNH0,M3x6MM | 4 NOS | AT "A" |
| | SCREW_PNH0,M3x6MM | 1 NO | AT "D" |
| 2 COVER KIT TOP COVER | SCREW_CSK M3x6MM,130DEG | 2 NOS | AT "B" |
| 3 INSULATOR MYLAR MYLAR M031 | TO BE PLACED UNDER THE PSU IN CK | 1 NO | BETWEEN PCB & CK BASE |
| 4 SYSTEM MTO (NOT SUPPLIED WITH COVER KIT) | SCREW_THREAD M3x0.5 3.0 MM MAX.PENETRATION | 2 NOS | AT "C" |

| *ITEM NO 3 PART DETAILS. | | |
|--------------------------|------------|---|
| MANUFACTURER | MPN | DESCRIPTION |
| DUPONT TEIJIN FILMS USLP | MYLAR M031 | POLYETHYLENE TERPHTHALTE(PET)MYLAR MIN THK 0.25MM,VTM-2 |

ULP40-CK.
MECHANICAL OUTLINE DIMENSIONS.