UL Product iQ®



Fuses, Supplemental Certified for Canada - Component

COMPANY

BEL FUSE INC

300 Executive Dr. Ste 300 West Orange, NJ 07052 United States

E20624

Marking: Company name model designation, and the Recognized Component Mark for Canada C Note: For additional marking information, refer to the Guide Information Page.

View model for additional information

Supplemental fuses, Model(s): 2JQ, 2JQ-R, 2JS, 2JS-R, 300V, BER

Supplemental fuses, Model(s): <u>0VMIN</u> followed by 4 digits (indicates amp rating), followed by 3 digits, which may be dashes, numbers or letters (indicates packaging and nonelectrical options)

Supplemental fuses: cartridge enclosed, Model(s): 33G, 3SF, 5ET, 5ET-R, 5SF, 5SF-R, 5ST, 5ST-R, 5TT, 5TT-R, 5VT, 5VT-R

Supplemental fuses: filled-tube, Model(s): <u>OADA</u>, <u>5HF, 5HF-R</u>

Supplemental fuses: filled-tube, cartridge enclosed, Model(s): <u>OADV</u>, <u>GSM</u>

Supplemental fuses: filled-tube, surface mount, cartridge enclosed, Model(s): <u>0ACF-0750-TE</u>, <u>0ACF-1000-TE</u>, <u>0ACF-2000-TE</u>, <u>0ACF-2000-TE</u>, <u>0ACF-2000-TE</u>, <u>0ACF-3000-TE</u>, <u>0ACF-3000-TE</u>

Supplemental fuses: filled-tube, surface mount, cartridge enclosed, Model(s): <u>OACJ</u> followed by followed by 4 digits (indicates amp rating from 0.5-7.5), followed by 3 digits, which may be dashes, numbers or letters (indicates packaging and non-electrical options).

Supplemental fuses: pigtail leads, Model(s): 300VP, 3JQ, 3JQ-R, 3JS, 3JS-R, 5HFP, 5HFP-R, 5JQ, 3JQ-P, 0657P(\$), DJB

Supplemental fuses: pigtail leads, cartridge enclosed, Model(s): <u>33P</u>, <u>3SFP</u>, <u>5ETP</u>, <u>5ETP</u>, <u>5SFP</u>, <u>5SFP</u>, <u>5SFP</u>, <u>5STP</u>-R, <u>5STP</u>, <u>5STP</u>-R, <u>5TTP</u>, <u>5TTP</u>-R, <u>5TTP</u>-R

Supplemental fuses: pigtail leads, filled-tube, Model(s): <u>OADB</u>

Supplemental fuses: pigtail leads, filled-tube, cartridge enclosed, Model(s): 0659C, 0659P, 0ADE, 0ADE, 0ADK

Supplemental fuses: surface mount, Model(s): <u>OACA</u>

Supplemental micro fuses, Model(s): RRT, SMP, SMP (2.2A), SSQ, SSQ (0.1A - 7.0A)

Supplemental micro fuses: filled-tube, Model(s): MRF, MRFU

Supplemental micro fuses: filled-tube, surface mount, Model(s): MRF, MRFU

Supplemental micro fuses: pigtail leads, Model(s): MBQ, MBQP, MQ, MBS, MBSP, MS, RS, WP91813 L1 thru WP91813 L17

Supplemental micro fuses: pigtail leads, filled-tube, Model(s): RRQ, 0698Q, TCQ, TCQP

Supplemental micro fuses: pigtail leads, surface mount, cartridge enclosed, Model(s): 1SM*

Supplemental micro fuses: surface mount, Model(s): <u>OABA</u>, <u>OABB</u>

(\$) - followed by 4 digits (indicates amp rating), followed by 3 digits, which may be dashes, numbers or letters (indicates packaging and non-electrical options) rated 40A, 350 V ac

* - Followed by suffix numbers.

Note - Cat. Nos. with suffix -R indicates construction with lead-free solder.

Last Updated on 2024-04-23

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."