

Proprietary Information of:  bel POWER SOLUTIONS & PROTECTION <small>© 2018 BEL</small>	Title: EMC Declaration of Conformity	Document No. URR.03132	Rev. AD
---	--	----------------------------------	-------------------

List of Product P/N:

No.	P/N	No.	P/N
1	DM1001-7R	22	<i>DM1642-7RD9</i>
2	DM1001-7RA	23	DM1738-6R
3	DM1001-9R	24	<i>DM1743-7P</i>
4	DM1001-9RG	25	DM1901-7R
5	DM1060-7R	26	DM2027-7
6	DM1301-7R	27	DM2067-9D0A
7	DM1301-9R	28	DM2067-9D0AG
8	DM1301-9RG	29	DM2302-7
9	DM1501-7R	30	DM2302-9G
10	DM1501-9R	31	DM2320-7
11	DM1501-9RD8	32	DM2320-9
12	DM1501-9RD8G	33	DM2333-7
13	DM1601-7R	34	DM2333-9G
14	DM1601-9R	35	DM2540-7
15	DM1601-9RD7HG	36	DM2540-7A
16	DM1601-9RG	37	DM2540-7D4
17	DM1604-7RD0	38	DM2540-7P
18	DM1604-9RD0G	39	DM2540-9
19	DM1607-7R	40	DM2540-9G
20	DM1618-0R	41	DM2603-7
21	DM1626-5RD2	42	DM2606-6

Proprietary Information of:



Title:

EMC Declaration of Conformity

Document No.

URR.03132

Rev.

AD

No.	P/N	No.	P/N
43	DM2609-9D0	64	<i>DM3649-5D2</i>
44	DM2741-9G	65	DM3727-7
45	DM2881-5	66	<i>DM3786-7</i>
46	DM3020-7	67	DM7002-7R
47	DM3020-7D2	68	<i>DM7604-7R</i>
48	DM3023-0	69	DM8321-7D9
49	DM3038-0	70	DM9023-7
50	DM3040-7	71	DM9720-7
51	DM3040-9	72	DMZ3040-7
52	DM3157-7D0	73	
53	DM3248-7D0	74	
54	DM3248-9D0G	75	
55	DM3379-7D0	76	
56	DM3383-7	77	
57	DM3387-7	78	
58	DM3577-7	79	
59	DM3578-5	80	
60	DM3580-7	81	
61	DM3581-7	82	
62	DM3581-7	83	
63	DM3646-5D2HG	84	

Note: model names may be followed by suffix indicating non-EMC critical options.

Part Number Description

		CM	2	5	40	-9	E	P	D3	A	H	G
Operating input range V_i :	8 – 35 VDC	A										
	14 – 70 VDC	B										
	20 – 100 VDC	F										
	28 – 140 VDC	C										
	44 – 220 VDC	D										
	67 – 385 VDC	E										
	85 – 264 VAC, 88 – 372 VDC	L										
Series		M										
Number of outputs ⁴	1, 2, 3 ⁴											
Output 1, $V_{o1 \text{ nom}}$:	5.1 V	0, 1, 2										
	12 V	3										
	15 V	4, 5										
	24 V	6										
	other voltages	7, 8										
	48 V	9										
Single-output models (different specs.)		01 – 99										
Outputs 2, 3: $V_{o2 \text{ nom}}$, $V_{o3 \text{ nom}}$:	5.1 V	01 – 19										
	12 V	20 – 39										
	15 V	40 – 59										
	24 V	60 – 69										
	other voltages and specs.	21 – 99										
Ambient temperature range T_A :	-25 to 71 °C	-7										
	-40 to 71 °C	-9										
	customer-specific ...	-0, -5, -6, -8										
Auxiliary functions and options:												
	Inrush current limitation (CM, EM, LM)	E										
	Output voltage control input (single-output models)	R ²										
	Potentiometers for adjustment of output voltages	P ²										
	Save data signal (D0 – D9, to be specified)	D ¹										
	ACFAIL signal (V0, V2, V3, to be specified)	V ¹										
	Output voltage test sockets	A										
	Increased electric strength test voltage	H										
	Input fuse built-in (not accessible)	F ³										
	Coding strip at the connector	K										
	RoHS-compliant for all 6 substances	G										

¹ Option D excludes option V and vice versa

² Feature R is fitted to single-output models only. Option P excludes option R (and vice versa).

³ Only for FM1000

⁴ Models with 220 mm case length. Just add 6000 to the standard model number, e.g., DM3020-9AG → DM9020-9AG.

Note: The sequence of options must follow the order above. This part number description is descriptive only; it is not intended for creating part numbers.

NFND: Not for new designs Preferred for new designs.