



# CERTIFICATE



No. P22226622

**Applicant**

Bel Fuse Inc.  
206 Van Vorst St. Jersey City 7302  
United States of America

**Manufacturer**

Bel Fuse Inc.  
206 Van Vorst St. Jersey City 7302  
United States of America

**Factory**

BPS Asia Pacific Electronics (Shenzhen) Co., Ltd.  
Building# 6, Nanming Road, Gongming Town Huahong Xintong Industrial Park  
Guangming District Shenzhen 518108  
China

**Project Number**

PRJ0025801

**Product**

AC-DC switching power supply

**Model/Type Ref.**

SPACSCO-26G, Cisco P/N (CPN): 341-0415-XX, SPACSCO-34G, Cisco P/N (CPN): 341-0461-XX, SPACSCO-39G, Cisco P/N (CPN): 341-0495-XX, SPACSCO-41G, Cisco P/N(CPN): 341-0521 XX, 341-100587-XX, 341-100661-XX, 341-1799-XX, SPACSCO-43G, Cisco P/N(CPN): 341-0523-XX

**Ratings**

Input: 100-240 V~, 12-5 A, 50-60 Hz Output: V1: 12Vdc, 90A\*; V2: 3.3Vdc, 3A

**Trademark**



**Principal Characteristics**

X is alpha numeric character 0-9,a-Z  
\*Note: For models SPACSCO-26G, SPACSCO-34G, SPACSCO-39G only:  
V1 maximum output current: 90 A at 100-240 Vac, 45°C operating ambient and 120-240 Vac, 55°C ambient.  
V1 maximum output current is de-rated to 80 A at 100-120 Vac input voltage, 55°C operating ambient

A sample of the product was tested and found to be in conformity with

Safety EN IEC 62368-1:2020;A11

**Validity**

This certificate documents conformity with the standards shown, and also applies as license for use of Nemko's name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation.

New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.

**Additional Information**

**Build-in products** Compliance with requirements regarding building-in, protection against electric shock and Electromagnetic Compatibility (EMC) must be checked when the equipment is built-in a completed product or forms a part of a complete system.

**Additional model(s)**

(2) See page 2


*Jiyea Gim*

**Signature**

Jiyea Gim  
Certification Department

**Date of issue**

19 / 12 / 2022



[www.nemko.com](http://www.nemko.com)




# CERTIFICATE



No. P22226622

Product	AC-DC switching power supply
Variant No.	1
Model/Type Ref.	SPACSCO-44G, Cisco P/N(CPN): 341-100431-XX, 341-0522- XX, 341-100586-XX, 341-100662- XX, 341-1798- XX
Ratings	Input: 100-240 V~, 12-5 A, 50-60 Hz Output: V1: 12Vdc, 90A; V2: 3.3Vdc, 3A
Trademark (if different from page 1)	
Principal Characteristics	X is alpha numeric character 0-9,a-Z
Product	AC-DC switching power supply
Variant No.	2
Model/Type Ref.	PET1300-12-054NA
Ratings	Input: 100-240 V~ 12-6 A 50-60 Hz Output: V1: 12Vdc, 108A*; V2: 3.3Vdc, 3A
Trademark (if different from page 1)	
Principal Characteristics	The model name maybe followed by alpha numeric characters indicating non-safety critical options *Note: V1 output current: derated to max 90 A at 90-108 Vac (100Vac nominal) input, 45°C operating ambient. V1 is maximum 108 A at 108V-264 Vac (120-240Vac nominal) input, 45°C operating ambient.

*Jiyea Gim*



[www.nemko.com](http://www.nemko.com)

Signature

Jiyea Gim

Date of issue

Certification Department

19 / 12 / 2022

Working for a more sustainable future- Please do not print

Page 2 of 2