

No. P23226985/A1

Applicant Bel Fuse Inc.
206 Van Vorst St. Jersey City 07302
United States of America

Manufacturer Bel Fuse Inc.
206 Van Vorst St. Jersey City 07302
United States of America

Factory BPS Asia Pacific Electronics (Shenzhen) Co., Ltd.
Building# 6, Nanming Road, Gongming Town Huahong Xintong Industrial Park
Guangming District Shenzhen 518108
China

Project Number PRJ0033198

Product AC-DC Converter, AC/DC-DC Converter

Model/Type Ref. PET2000-12-074NA, PET2000-12-074NAA, PET2000-12-074NAC, SPADSSD-02G, SPAXYZ-01G, PET2000-12-074NACS354 (Cisco P/N (CPN): 341-100362-01), PET2000-12-074NACS373 (Cisco P/N (CPN): 341-100362-XY), PET2000-12-074NAS454

Ratings Input: 100-127V~/200-240 V~, 12 A, 50/60 Hz Output: V1: 12 Vdc, 83.3 A max.(100-127V~), 167 A max.(200-240V~) VSB: 12.15 V, 5 A max.

Trademark 

Principal Characteristics The model may be followed by alpha numeric characters indicating non-safety critical options. The X is alpha numeric character 0-9, a-Z.
The Y is alpha numeric character 2-9, a-Z

A sample of the product was tested and found to be in conformity with **Safety** EN IEC 62368-1:2020;A11

Replaces This certificate replaced previous certificate No. P23226985, due to misprint in model name.

Validity This certificate documents conformity with the standards shown, and also applies as license for use of Nemko's name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation.


New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.

Additional Information

Build-in products Compliance with requirements regarding building-in, protection against electric shock and Electromagnetic Compatibility (EMC) must be checked when the equipment is built-in a completed product or forms a part of a complete system.

Additional model(s) (11) See page 2

Jiyea Gim



www.nemko.com

Signature Jiyea Gim

Certification Department

Date of issue 13 / 04 / 2023

Working for a more sustainable future- Please do not print

No. P23226985/A1

Product	AC-DC Converter, AC/DC-DC Converter
Variant No.	1
Model/Type Ref.	PET2000-NAS446
Ratings	Input: 100-127V~/200-240 V~, 12 A, 50/60 Hz Output: V1: 12 Vdc, 83.3 A max.(100-127V~), 167 A max.(200-240V~) VSB: 12.15 V, 3 A max
Trademark (if different from page 1)	
Principal Characteristics	The model may be followed by alpha numeric characters indicating non-safety critical options.
Product	AC-DC Converter, AC/DC-DC Converter
Variant No.	2
Model/Type Ref.	SPACSCO-50G (Cisco P/N (CPN): 341-100516-XX, 341-100948-XX); SPACSCO-51G (Cisco P/N (CPN): 341-100514-XX, 341-100949-XX)
Ratings	Input: 100-127V~/200-240 V~, 12 A, 50/60 Hz Output: V1: 12 Vdc, 83.3 A max.(100-127V~), 167 A max. (200-240V~) VSB: 12 V, 3 A max.
Trademark (if different from page 1)	
Principal Characteristics	The model may be followed by alpha numeric characters indicating non-safety critical options. The X is alpha numeric character 0-9, a-Z.
Product	AC-DC Converter, AC/DC-DC Converter
Variant No.	3
Model/Type Ref.	SPACSCO-50GRC (Cisco P/N (CPN): 341-1888-XX); SPACSCO-51GRC (Cisco P/N (CPN): 341-1800-XX)
Ratings	Input: 200-240 V~, 12 A, 50/60 Hz Output: V1: 12 Vdc, 167 A max. VSB: 12 V, 3 A max.
Trademark (if different from page 1)	
Principal Characteristics	The model may be followed by alpha numeric characters indicating non-safety critical options. The X is alpha numeric character 0-9, a-Z.

Jiyea Gim

Signature

Jiyea Gim

Date of issue

Certification Department
13 / 04 / 2023



www.nemko.com

Page 2 of 5

No. P23226985/A1

Product	AC-DC Converter, AC/DC-DC Converter
Variant No.	4
Model/Type Ref.	PET1600-12-074NA; SPADSSD-01G
Ratings	Input: 100-127V~/200-240 V~, 12/10 A, 50/60 Hz Output: V1: 12 Vdc, 83.3 A max. (100-127V~), 133 A max.(200-240V~) VSB: 12.15 V, 4 A max.
Trademark (if different from page 1)	
Principal Characteristics	The model may be followed by alpha numeric characters indicating non-safety critical options.
Product	AC-DC Converter, AC/DC-DC Converter
Variant No.	5
Model/Type Ref.	PET2000-12-074RA, PET2000-12-074RAS455
Ratings	Input: 100-127V~/200-240 V~, 12 A, 50/60 Hz Output: V1: 12 Vdc, 83.3 A max.(100-127V~), 167 A max. (200-240V~) VSB: 12 V, 3 A max.
Trademark (if different from page 1)	
Principal Characteristics	The model may be followed by alpha numeric characters indicating non-safety critical options.
Product	AC-DC Converter, AC/DC-DC Converter
Variant No.	6
Model/Type Ref.	SPACSCO-56G (Cisco P/N (CPN): 341-100657-XX, 341-101003-XX, 341-1806-XX, 341-100950- XX); SPACSCO-56GKD, SPACSCO-56GKD1, SPACSCO-56GKD3, SPACSCO- 56GKD4, SPACSCO-56GKD5 (Cisco P/N (CPN): 341-101456-XX)
Ratings	Input: 100-127V~, 12A, 200-277 V~, 12 A, 50/60 Hz, 240-380Vdc, 12A Output: V1: 12 Vdc, 83.3 A max. (100-127Vac), 167 A max. (200-277Vac, 240-380Vdc), VSB: 12 Vdc, 3 A max
Trademark (if different from page 1)	
Principal Characteristics	The model may be followed by alpha numeric characters indicating non-safety critical options. The X is alpha numeric character 0-9, a-Z.

Jiyea Gim

Signature

Jiyea Gim

Date of issue

Certification Department

13 / 04 / 2023

Working for a more sustainable future- Please do not print



www.nemko.com

Page 3 of 5

No. P23226985/A1

Product	AC-DC Converter, AC/DC-DC Converter
Variant No.	7
Model/Type Ref.	SPACSCO-56GKD6, SPACSCO-56GKD7, SPACSCO-56GKD8, SPACSCO-56GKD9 (Cisco P/N (CPN): 341-101456-XX), SPACSCO-57G (Cisco P/N (CPN): 341-100656-XX, 341-100951-XX), PET2000-12-074NH, PET2000-12-074RH
Ratings	Input: 100-127V~, 12A, 200-277 V~, 12 A, 50/60 Hz, 240-380Vdc , 12A Output: V1: 12 Vdc, 83.3 A max. (100-127Vac), 167 A max. (200-277Vac, 240-380Vdc), VSB: 12 Vdc, 3 A max.
Trademark (if different from page 1)	
Principal Characteristics	The model may be followed by alpha numeric characters indicating non-safety critical options. The X is alpha numeric character 0-9, a-Z.
Product	AC-DC Converter, AC/DC-DC Converter
Variant No.	8
Model/Type Ref.	SPACSCO-58G (Cisco P/N (CPN): 341-100704-XX)
Ratings	Input: 100-127V~, 14A, 200-240 V~, 10 A, 50/60 Hz Output: V1: 12 Vdc, 100 A max.(100-127V~), 133 A max. (200-240V~) VSB: 12 Vdc, 3 A max.
Trademark (if different from page 1)	
Principal Characteristics	The model may be followed by alpha numeric characters indicating non-safety critical options. The X is alpha numeric character 0-9, a-Z.
Product	AC-DC Converter, AC/DC-DC Converter
Variant No.	9
Model/Type Ref.	SPACSCO-66 (Cisco P/N (CPN): 341-100789-XX, 341-101198-XX)
Ratings	Input: 100-127V~, 12A, 200-240 V~, 10 A, 50/60 Hz Output: V1: 12 Vdc, 87.5 A max.(100-127V~), 133 A max. (200-240V~) VSB: 12 Vdc, 3 A max. Total output power: 1068 W @ 100-127 V~ 1632 W @ 200-240 V~
Trademark (if different from page 1)	
Principal Characteristics	The model may be followed by alpha numeric characters indicating non-safety critical options. The X is alpha numeric character 0-9, a-Z.

Jiyea Gim

Signature

Jiyea Gim

Date of issue

Certification Department
13 / 04 / 2023



www.nemko.com

Page 4 of 5



CERTIFICATE



No. P23226985/A1

Product	AC-DC Converter, AC/DC-DC Converter
Variant No.	10
Model/Type Ref.	SPACSCO-67 (Cisco P/N (CPN): 341-100792-XX)
Ratings	Input: 100-127V~ 12A, 200-240V~ 12A, 50/60 Hz Output: V1: 12 Vdc, 87.5 A max. (100-127V~), 167 A max. (200-240V~), VSB: 12 Vdc, 3 A max. Total output power: 1068 W @ 100-127V~, 2036 W @ 200-240 V~
Trademark (if different from page 1)	
Principal Characteristics	The model may be followed by alpha numeric characters indicating non-safety critical options. The X is alpha numeric character 0-9, a-Z.
Product	AC-DC Converter, AC/DC-DC Converter
Variant No.	11
Model/Type Ref.	SPACSCO-56GKD2 (Cisco P/N (CPN): 341-101446-XX)
Ratings	Input: 100-127V~, 12A, 200-277 V~, 12 A, 50/60 Hz, 240-380Vdc, 12A Output: V1: 12 Vdc, 83.3 A max. (100-127Vac), 167 A max. (200-277Vac, 240-380Vdc), VSB: 12 Vdc, 3 A max
Trademark (if different from page 1)	
Principal Characteristics	The model may be followed by alpha numeric characters indicating non-safety critical options. The X is alpha numeric character 0-9, a-Z.

Jiyea Gim

Signature

Jiyea Gim

Date of issue

Certification Department

13 / 04 / 2023

Working for a more sustainable future- Please do not print



www.nemko.com

Page 5 of 5